OAK - ANTIQUE

Antique Collection

FORESTRY TIMBER

Hardwood flooring engineered for living, **Designed to impress**

INDOOR AIR QUALITY		PERFORMANCE
	EN 16516:2017 **ISO 16000 3, 6, 9, 11** **ASTM D5116-10**	
	Émissions dans l'air intérieur A+ Label (France) Volatile Organic Compound (VOC)	A+
LEED® v4.1	Building Design & Construction	Meets requirements on some products
AgBB Evaluation	Committee for Health-Related Evaluation of Building products (Germany)	Meets requirements on some products
BREEAM® International	BREEAM® International New Construction v2 (2016)	Exemplary Level on some products
BREEAM® NOR	BREEAM® NOR New Construction v1.2 (2019)	Meets requirements on some products
	No Added Formaldehyde Guidelines, V3-0 (APRIL 2013)	No added compounds using urea formaldehyde or phenol formaldehyde in conformance to the SCS. Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350) Less than/equal to 0.5 mg/m³
	Indoor Air Quality (US Standard)	Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350) Measured Concentration of Total Volatile Organic Compounds (TVOC): Less than/equal to 0.5 mg/m³
NO FORMALDEHYDE	EN 14342:2013 EN 717-1	F☆☆☆☆~ SE0 ≤ 0,034 mg/m³

TESTED & CERTIFIED		PERFORMANCE
	CE (Conformité Européenne) European Standard EN 14342:2013	Compliant
	Sucofindo International Certification Services VLK 00041	Compliant

SUSTAINABILITY		CERTIFICATION BODY	PERFORMANCE
FSC®	FSC 100%; FSC Mix; FSC Controlled Wood *FTE SCS-COC-008307 *FTF SCS-COC-008305 *FTX SCS-COC-008306 *FTR SGSHK-COC-006228	SCS Global Services SGS Hong Kong	Available on request
PEFC™	PEFC Certified and PEFC Controlled sources sawn timber and engineered flooring *FTE SGS-PEFC/COC-MY21/1811030547 *FTF SGS-PEFC/COC-MY21/1811030548 *FTX SGS-PEFC/COC-MY21/1811030546 *FTR SGS-PEFC/COC-MY18/1102977975	SGS Malaysia	Available on request

FORESTRY TIMBER

Hardwood flooring engineered for living, **Designed to impress**

HARDWOOD ENGINEERED FLOORING

Species	Western European Oak
Surface Texture	Smooth, brushed or distressed
Finish	UV Urethane Bona UV Oil UV Urethane HP
Grade	Antique
Construction	Three-layered Engineered planks with Hevea Core

DIMENSIONS

Thickness	14.2mm	or	22mm			
	9/16”	or	7/8”			
Plank Widths	145mm	190mm	240mm	290mm	340mm	400mm
	5 3/4”	7 1/2”	9 1/2”	11 1/2”	13 7/16”	15 3/4”
Plank Length	2130mm	2450mm	3000mm			
	7’	8’	9’ 9/10”			
Herringbone	120mm	x	840mm			
	4 ¾”	x	2’ 9”			
Chevron Single Plank	120mm	x	770mm			
	4 ¾”	x	2’ 6”			
Chevron Connex	240mm	x	1450mm			
	9 ½”	x	4’ 9”			

INSTALLATION

Engineered Planks	Tongue & Groove - Välinge 5G Installation Tongue & Groove Floating, Glue or Nail down

USAGE		
	Recommended Installation	Suitable for use in residential projects. For commerical projects we recommend additional treatments

SLIP RATING		PERFORMANCE
	EN 14342:2013 CEN/TS 15676	PTV 45 (UV Bona) PTV 44 (UV Oil) UV HP - ASTM D4060/DIN EN438 *PTV = Mean pendulum swing value*

FIRE RATING		PERFORMANCE
	EN 14342:2013 EN 13501-1	14.2mm Class D_{fl} - s1 22mm Class C_{fl} -s1

*FTE - FTE International LTD
*FTF - Forestry Timber Flooring International LTD
*FTX - Forestry Timber Export Sdn Bhd
*FTR - Forestry Timber Resources Sdn Bhd

FORESTRY TIMBER

Hardwood flooring engineered for living,
Designed to impress