

OAK - ANTIQUE

Antique Collection



Hardwood flooring
engineered for living,
Designed to impress

INDOOR AIR QUALITY PERFORMANCE

	EN 16516:2017 ISO 16000 3, 6, 9, 11 ASTM D5116-10	
	Émissions dans l'air intérieur A+ Label (France) Volatile Organic Compound (VOC)	A+
LEED® v4.1	Building Design & Construction	Meets requirements on some products
AgBB Evaluation	Committee for Health-Related Evaluation of Building products (Germany)	Meets requirements on some products
BREEAM® International	BREEAM® International New Construction v2 (2016)	Exemplary Level on some products
BREEAM® NOR	BREEAM® NOR New Construction v1.2 (2019)	Meets requirements on some products
	No Added Formaldehyde Guidelines, V3-0 (APRIL 2013)	No added compounds using urea formaldehyde or phenol formaldehyde in conformance to the SCS. Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350) Less than/equal to 0.5 mg/m ³
	Indoor Air Quality (US Standard)	Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350) Measured Concentration of Total Volatile Organic Compounds (TVOC): Less than/equal to 0.5 mg/m ³
NO FORMALDEHYDE	EN 14342:2013 EN 717-1	F☆☆☆☆~ SE0 ≤ 0,034 mg/m ³






TESTED & CERTIFIED PERFORMANCE

	CE (Conformité Européenne) European Standard EN 14342:2013	Compliant
	Sucofindo International Certification Services VLK 00041	Compliant







SUSTAINABILITY CERTIFICATION BODY PERFORMANCE

	FSC 100%; FSC Mix; FSC Controlled Wood SCS-COC-008306	SCS Global Services	Available on request
	PEFC Certified and PEFC Controlled soursawn timber and engineered flooring SGS-PEFC/COC-MY21/181103546	SGS Malaysia	Available on request


HARDWOOD ENGINEERED FLOORING

	Species	Western European Oak
	Surface Texture	Smooth, brushed or distressed
	Finish	UV Urethane Bona UV Oil UV Urethane HP
	Grade	Antique
	Construction	Three-layered Engineered planks with Hevea Core

DIMENSIONS

	Thickness	14.2mm or 22mm 9/16" or 7/8"
	Plank Widths	145mm 190mm 240mm 290mm 340mm 400mm 5 3/4" 7 1/2" 9 1/2" 11 1/2" 13 7/16" 15 3/4"
	Plank Length	2130mm 2450mm 3000mm 7' 8' 9' 9/10"
	Herringbone	120mm x 840mm 4 3/4" x 2' 9"
	Chevron Single Plank	120mm x 770mm 4 3/4" x 2' 6"
	Chevron Connex	240mm x 1450mm 9 1/2" x 4' 9"

INSTALLATION

	Engineered Planks	Tongue & Groove - Välinge 5G Installation Tongue & Groove Floating, Glue or Nail down
---	-------------------	---

USAGE



Recommended Installation

Suitable for use in residential projects. For commercial projects we recommend additional treatments

SLIP RATING

PERFORMANCE



EN 14342:2013
CEN/TS 15676

PTV 45 (UV Bona)
PTV 44 (UV Oil)
UV HP - ASTM D4060/DIN EN438
PTV = Mean pendulum swing value

FIRE RATING

PERFORMANCE



EN 14342:2013
EN 13501-1

14.2mm Class D_{fl} - s1
22mm Class C_{fl} -s1



FORESTRY
TIMBER

*Hardwood flooring
engineered for living,
Designed to impress*