





TASMANIAN OAK

After Oak Collection





Hardwood flooring
engineered for living,
Designed to impress


INDOOR AIR QUALITY PERFORMANCE

	EN 16516:2017 ISO 16000 3, 6, 9, 11 ASTM D5116-10	
	Émissions dans l'air intérieur A+ Label (France) Volatile Organic Compound (VOC)	A+
LEED® v4.1	Building Design & Construction	Meets requirements on some products
AgBB Evaluation	Committee for Health-Related Evaluation of Building products (Germany)	Meets requirements on some products
BREEAM® International	BREEAM® International New Construction v2 (2016)	Exemplary Level - on some products
BREEAM® NOR	BREEAM® NOR New Construction v1.2 (2019)	Meets requirements on some products
	No Added Formaldehyde Guidelines, V3-0 (APRIL 2013)	No added compounds using urea formaldehyde or phenol formaldehyde in conformance to the SCS. Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350) Less than/equal to 0.5 mg/m ³
	Indoor Air Quality (US Standard)	Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350) Measured Concentration of Total Volatile Organic Compounds (TVOC): Less than/equal to 0.5 mg/m ³
NO FORMALDEHYDE	EN 14342:2013 EN 717-1	F☆☆☆☆~ SE0 ≤ 0,034 mg/m ³

TESTED & CERTIFIED PERFORMANCE

	CE (Conformité Européenne) European Standard EN 14342:2013	Compliant
	Sucofindo International Certification Services VLK 00041	Compliant





SUSTAINABILITY CERTIFICATION BODY PERFORMANCE

	PEFC Certified and PEFC Controlled sources sawn timber and engineered flooring SGS-PEFC/COC-MY21/181103546	SGS Malaysia	Available on request
---	--	--------------	----------------------


HARDWOOD ENGINEERED FLOORING

	Species	Tasmanian Oak
	Surface Texture	Smooth
	Finish	UV Urethane Bona UV Oil UV Urethane HP
	Grade	Rustic
	Construction	Three-layered Engineered planks with Hevea Core

DIMENSIONS

	Thickness	14.2mm or 22mm 5/16" or 7/8"
	Plank Widths	190mm 6 1/2"
	Plank Length	2130mm 7'
	Herringbone	120mm x 840mm 4 3/4" x 2' 9"
	Chevron Single Plank	120mm x 770mm 4 3/4" x 2' 6"

INSTALLATION

	Engineered Planks	Tongue & Groove - Välinge 5G Installation Tongue & Groove Floating, Glue or Nail down
---	-------------------	---

USAGE



Recommended Installation

Suitable for use in residential projects. For commercial projects we recommend additional treatments

SLIP RATING

PERFORMANCE



EN 14342:2013
CEN/TS 15676

PTV 45 (UV Bona)
PTV 44 (UV Oil)
UV HP - ASTM D4060/DIN EN438
PTV = Mean pendulum swing value

FIRE RATING

PERFORMANCE



EN 14342:2013
EN 13501-1

14.2mm Class D_{fl} - s1
22mm Class C_{fl} -s1



FORESTRY
TIMBER

*Hardwood flooring
engineered for living,*
Designed to impress