










INDOOR AIR QUALITY		PERFORMANCE
	EN 16516:2017 ISO 16000 3, 6, 9, 11 ASTM D5116-10	
	Émissions dans l'air intérieur A+ Label (France) Volatile Organic Compound (VOC)	A+
LEED® v4.1	Building Design & Construction	Meets requirements on some products
AgBB Evaluation	Committee for Health-Related Evaluation of Building products (Germany)	Meets requirements on some products
BREEAM® International	BREEAM® International New Construction v2 (2016)	Exemplary Level on some products
BREEAM® NOR	BREEAM® NOR New Construction v1.2 (2019)	Meets requirements on some products
	No Added Formaldehyde Guidelines, V3-0 (APRIL 2013)	No added compounds using urea formaldehyde or phenol formaldehyde in conformance to the SCS. Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350) Less than/equal to 0.5 mg/m <sup>3</sup>
	Indoor Air Quality (US Standard)	Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350) Measured Concentration of Total Volatile Organic Compounds (TVOC): Less than/equal to 0.5 mg/m <sup>3</sup>
NO FORMALDEHYDE	EN 14342:2013 EN 717-1	F☆☆☆☆~ SE0 ≤ 0,034 mg/m <sup>3</sup>







TESTED & CERTIFIED		PERFORMANCE
	CE (Conformité Européenne) European Standard EN 14342:2013	Compliant
	Sucofindo International Certification Services VLK 00041	Compliant

SUSTAINABILITY	CERTIFICATION BODY	PERFORMANCE
	FSC 100%; FSC Mix; FSC Controlled Wood SCS-COC-008306	SCS Global Services Available on request
	PEFC Certified and PEFC Controlled sources sawn timber and engineered flooring SGS-PEFC/COC-MY21/181103546	SGS Malaysia Available on request


## HARDWOOD ENGINEERED FLOORING

	Species	European Ash
	Surface Texture	Smooth
	Finish	UV Urethane Bona UV Oil UV Urethane HP
	Grade	Rustic
	Construction	Three-layered Engineered planks with Hevea Core

## DIMENSIONS

	Thickness	14.2mm or 22mm $\frac{9}{16}$ " or $\frac{7}{8}$ "
	Plank Widths	190mm $7\frac{1}{2}$ "
	Plank Length	2130mm 7'
	Herringbone	120mm x 840mm $4\frac{3}{4}$ " x 2' 9"
	Chevron Single Plank	120mm x 770mm $4\frac{3}{4}$ " x 2' 6"
	Chevron Connex	240mm x 1450mm $9\frac{3}{4}$ " x 4' 9"

## INSTALLATION

	Engineered Planks	Tongue & Groove - Välinge 5G Installation Tongue & Groove Floating, Glue or Nail down
-------------------------------------------------------------------------------------	-------------------	---------------------------------------------------------------------------------------------

## USAGE



### Recommended Installation

Suitable for use in residential projects. For commercial projects we recommend additional treatments

## SLIP RATING



EN 14342:2013  
CEN/TS 15676

## PERFORMANCE

PTV 45 (UV Bona)  
PTV 44 (UV Oil)  
UV HP - ASTM D4060/DIN EN438  
*PTV = Mean pendulum swing value*

## FIRE RATING



EN 14342:2013  
EN 13501-1

## PERFORMANCE

14.2mm Class D<sub>fl</sub> - s1  
22mm Class C<sub>fl</sub> -s1



Hardwood flooring  
engineered for living,  
**Designed to impress**